

*ALL EXTERNAL PIPING MUST BE INDEPENDENTLY SUPPORTED.
*ONLY BASE FITTINGS TO BE LEFT INSTALLED AT TIME OF SHIPMENT PER SII PROCEDURE.
*Consult Snyder's Guidelines for Use and Installation prior to delivery.
Available on-line at http://www.snyderindustriestanks.com/Technical

ALL DIMENSIONS ARE IN INCHES, NOMINAL, & SUBJECT TO CHANGE WITHOUT NOTICE. ALL DIMENSIONS ON ROTATIONAL MOLDED PARTS ARE SUBJECT TO A \pm 3% TOLERANCE.

	DO NOT SCALE	DRAWN BY	DATE
STATUS:	Released	ET3	07/30/2013
© SNYDER INDUSTRIES INC., 2014			
CONSIDE BE USED,	NSIONS, DESIGNS, AND INFORMATI RED PROPRIETARY TO SNYDER INDU COPIED, OR DISTRIBUTED WITHOUT (OR HIS AGENT) OF THE FIRM.	ISTRIES, INC. At	TON YAM ON

4700 Fremont Street Lincoln, NE 68504 (402) 467-5221 www.snydernet.com ASM TK 550VDT X 64

PART NO. 1820000N__01 ENG. ID. D001110

Α

SHEET

1 OF 1