

CONTROL PANEL ACCESSORIES

Cord Seals, Hub Assembly, Simplex Installation Kit, Duplex Installation Kit, C-Level™ Simulator, 4-20mA Simulator, Sub-X™ Transmitter, Cable Connectors, Panel Mounting Post, and Riser Mounting Kit

CORD SEALS

Provides strain relief and a liquid-tight seal.

- Seals 1-4 cables in 2" terminal adapters
- Seals 1-6 cables in 2½" terminal adapters
- PVC plugs included (for unused cable positions)
- Ground wire



SEAL: neoprene

WASHERS: stainless steel

NUT AND BOLT: stainless steel

WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2, 18/3, 16/2, 16/3, 14/2 and 14/3

| Part Number | Description |
|-------------|---------------------------------|
| 1008517 | 2 inch Cord Seal (1-4 Cables) |
| 1037126 | 2.5 inch Cord Seal (1-6 Cables) |

C-LEVEL™ SIMULATOR

Easy-to-use, hand-held test instrument designed to generate an adjustable C-Level™ simulation signal.



| Part Number | Description |
|-------------|--------------------|
| 1038326 | C-Level™ Simulator |

4-20mA SIMULATOR

Easy-to-use, hand-held test instrument designed to generate an adjustable 4-20mA signal from loop power.



| Part Number | Description |
|-------------|------------------|
| 1039199 | 4-20mA Simulator |

SUB-X™ TRANSMITTER

Submersible level transmitter with 4-20mA output.

- Available in 7.25 PSI (16.7 ftWC) and 14.5 PSI (33.4 ftWC) ranges
- Includes mounting bracket



US Patent
8,336,385

| Part Number | Description |
|-------------|-----------------------------------|
| 1051995 | Sub-X™ 16.7 ftWC with 25ft cable |
| 1051993 | Sub-X™ 16.7 ftWC with 50ft cable |
| 1051992 | Sub-X™ 16.7 ftWC with 75ft cable |
| 1051991 | Sub-X™ 16.7 ftWC with 100ft cable |
| 1051996 | Sub-X™ 33.4 ftWC with 25ft cable |
| 1051989 | Sub-X™ 33.4 ftWC with 50ft cable |
| 1051990 | Sub-X™ 33.4 ftWC with 75ft cable |
| 1051994 | Sub-X™ 33.4 ftWC with 100ft cable |

California Prop 65 requires the following: WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov

**PRODUCTS CONTINUED ON NEXT PAGE.
SEE PRICE BOOK FOR LIST PRICES.**

SIMPLEX INSTALLATION KIT

Provides easy weather-proof wire installation for simplex control panels.

Includes:

- 2" hub assembly
- 2" cord seal (seals 1-4 cables)
- ¾" hub assembly



| Part Number | Description |
|-------------|---------------------------|
| 1038029 | Installation Kit, Simplex |

DUPLEX INSTALLATION KIT

Provides easy weather-proof wire installation for duplex control panels.

Includes:

- 2.5" hub assembly
- 2.5" cord seal (seals 1-6 cables)
- ¾" hub assembly



| Part Number | Description |
|-------------|--------------------------|
| 1038030 | Installation Kit, Duplex |

HUB ASSEMBLY

Provides liquid-tight conduit attachment location.

- Available in ¾, 1, 1.5, 2 and 2.5 inch sizes.
- UL Listed and CSA Certified terminal adapter



TERMINAL ADAPTER (HUB): PVC

GASKET: neoprene

LOCK NUT: metal

| Part Number | Description |
|-------------|-----------------------|
| 1030564 | ¾ inch Hub Assembly |
| 1009305 | 1 inch Hub Assembly |
| 1008848 | 1.5 inch Hub Assembly |
| 1008849 | 2 inch Hub Assembly |
| 1037128 | 2.5 inch Hub Assembly |



SJE RHOMBUS.

1-888-DIAL-SJE • 1-218-847-1317

1-218-847-4617 Fax

email: customer.service@sjeinc.com

www.sjerhombus.com

CONTROL PANEL ACCESSORIES

Cord Seals, Hub Assembly, Simplex Installation Kit, Duplex Installation Kit, C-Level™ Simulator, 4-20mA Simulator, Sub-X™ Transmitter, Cable Connectors, Panel Mounting Post, and Riser Mounting Kit

CABLE CONNECTORS

Provides strain relief and a liquid-tight seal.

- UL Listed and CSA Certified



VDE Approved




ROUND CABLE SPECIFICATIONS

MATERIAL: polyimid flame-resisting, self-extinguishing plastic

O RING: neoprene plastic

HOLE REQUIREMENT: NPT threaded OR clearance holes (jam nut included)



RCC-8

NPT Hub: .5 inch (1.27cm)

Maximum Diameter: .480 inch (1.22 cm)

Minimum Diameter: .270 inch (.68 cm)

Wire/Cable (AWG) Accommodated: 18/2, 18/3, 18/4, 16/2,

16/3, 16/4, 14/2, and 14/3

RCC-12

NPT Hub: .75 inch (1.90 cm)

Maximum Diameter: .709 inch (1.80 cm)

Minimum Diameter: .545 inch (1.38 cm)

Wire/Cable (AWG) Accommodated: 14/2, 14/3, 14/4, 12/2,

12/3, 12/4, 10/2, and 10/3

RCC-16

NPT Hub: 1.0 inch (2.54 cm)

Maximum Diameter: .98 inch (2.49 cm)

Minimum Diameter: .71 inch (1.80 cm)

Wire/Cable (AWG) Accommodated: Round cable with outside diameter within range identified above.


| Part Number | Description |
|-------------|---|
| 1002574 | 1/2 inch Round Cable Connector (RCC-8) |
| 1002575 | 3/4 inch Round Cable Connector (RCC-12) |
| 1009868 | 1 inch Round Cable Connector (RCC-16) |

FLAT UF CABLE SPECIFICATIONS

MATERIAL: weather-stabilized thermo plastic

O RING: neoprene plastic

HOLE REQUIREMENT: NPT threaded OR clearance holes (jam nut included)



UFCC-8

NPT Hub: .50 inch (1.27 cm)

Maximum: .26 x .56 inch (.66 - 1.42 cm) slot

Wire/Cable (AWG) Accommodated: 14/2, 12/2, 10/2

UFCC-12

NPT Hub: .75 inch (1.90 cm)

Maximum: .26 x .60 inch (.66 - 1.52 cm) slot

Wire/Cable (AWG) Accommodated: 14/3, 12/3

| Part Number | Description |
|-------------|--|
| 1002576 | 1/2 inch Flat UF Cable Connector (UFCC-8) |
| 1002577 | 3/4 inch Flat UF Cable Connector (UFCC-12) |

PANEL MOUNTING POST

Provides easy installation of control panels.

- Removable front access door for easy wiring
- Can be mounted directly into ground, over a 4x4 post, or conduit for a quick, clean, easy installation
- Includes 4 stainless steel mounting bolts
- Includes drilling template
- Accommodates enclosures up to 14 x 12 x 6 inches (35.6 x 30.5 x 15.2 cm)



POST: Polyethylene (34 x 7 x 6 inches)

BOLTS: 4X rated stainless steel with gaskets

| Part Number | Description |
|-------------|---------------------|
| 1038027 | Panel Post Assembly |

RISER MOUNTING KIT

Secures panel mounting post to tank riser.

Includes:

- (2) hub assemblies
- PVC pipe and connecting hardware
- Conduit for routing pump and float from tank riser to post



unassembled



assembled

| Part Number | Description |
|-------------|-------------------------------|
| 1038262 | Riser Mounting Kit (2 inch) |
| 1053756 | Riser Mounting Kit (2.5 inch) |

www.sjrhombus.com
customer.service@sjeinc.com

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) • Fax 218-847-4617

Product offering and pricing are subject to change without notice.

H.6 Please visit www.sjrhombus.com for the most current information.